

OA Series

The OA Series is a full-color commercial advertising billboard with an outdoor fixed digital LED display screen featuring a white design that supports full front or rear service
Pixel pitch options: 4.4mm, 5.7mm, 6.67mm, 8mm, 10mm



Seamless
splicing



High brightness



High contrast



Low energy



IP 66



Exquisite Cabinet Design

Concealed Power and Signal Design - Clean and streamlined appearance

White Appearance and Aluminum Alloy Material - Better heat dissipation

Safety Rope Design - Easy and secure replacement

Excellent Fire Resistance



Elite Performance and Features

Ultra Thin, Lightweight - Easy to install

Front & Rear Maintenance - Easy maintenance

High Waterproof Rating - Suitable for various outdoor applications



The average power consumption <85w/m²
Light intensity 500CD/m²



Low power



Low heat



Specification:

Model	OA-4.4	OA-5.7	OA-6.67	OA-8	OA-10
Physical Pitch	4.4mm/0.17"	5.7mm/0.22"	6.67mm/0.26"	8mm/0.34"	10mm/0.39"
Pixel Configuration	SMD1921	SMD2727	SMD2727	SMD2727	SMD2727
Pixel Density	50625px/m ²	30625px/m ²	22500px/m ²	15625px/m ²	10000px/m ²
Module Dimension(WxHxD)	480x320x14mm	480x320x15mm	480x320x16mm	480x320x16mm	480x320x18mm
Panel Dimension(WxHxD)	960x960x84mm	960x960x85mm	960x960x86mm	960x960x86mm	960x960x88mm
No. of Module/panel(WxH)	2x3				
Module Resolution	108x72px	84x56px	72x48px	60x40px	48x32px
Panel Resolution	216x216px	168x168px	144x144px	120x120px	96x96px
Panel Material	Aluminum alloy				
Panel Weight	26.5kg(58.42lbs)				
Gray Scale	16bit				
Contrast Ratio	15000:1				
Avg. Power Consumption	186w/m ²				
Max. Power Consumption	550w/m ²				
Operating Temp/Humidity	-10°C - 60°C / 10% - 60%				
Storage Temp/Humidity	-30°C - 60°C / 10% - 60%				
Refresh Rate	3840hz				
Brightness	6000nits/10000nits				
Viewing Angle(H/V)	140°/120°				
Expected Lifetime	100,000hrs				
Service	Front & Rear				
IP Rating(Front/Rear)	IP66				
Certification	CCC,CE,ETL,RoHS				

