

TS-R Series

Ultra-thin panel design, lightweight, and with high transparency

Unlimited orientation, highly customized, suitable for any size and shape

Outstanding permeability: Offers superior airflow and light transmission, reduced wind resistance, and excellent ventilation performance



Seamless
Splicing



Transparency



Ultra-Light



Low Energy



IP 65




Outdoor Rental LED Screen

Durable & weatherproof, interactive content with great flexibility

Easily customized in type, size, and quantity

Air permeability – Incorporate ventilation features to improve airflow while maintaining visibility



Easy to Install, Dismantle

Hanging brackets for quick setup – minimizing time and labor costs


Front & Rear Maintenance – easy access for quick servicing




Fast Lock



Detachable Power Box



Corner Protector



Transparency

Specification:

Model

TSR-3.9-7.8

Physical Pitch	3.9-7.8mm/0.15"-0.30"
Pixel Configuration	SMD1921
Pixel Density	32768px/m ²
Module Dimension(WxH)	500x125mm/19.68"x4.92"
Panel Dimension(WxHxD)	500x1000mm/19.68"x39.37"
No. of Module/panel(WxH)	1x8
Module Resolution	128x16px
Panel Resolution	128x128px
Panel Material	Aluminum alloy
Panel Weight	9KG per panel(19.85lbs)
Gray Scale	16bit
Contrast Ratio	6000:1
Avg. Power Consumption	180w/m ²
Max. Power Consumption	560w/m ²
Operating Temp/Humidity	-10°C - 60°C / 10% - 60%
Storage Temp/Humidity	-30°C - 60°C / 10% - 60%
Refresh Rate	7680hz
Brightness	≥ 5500nits
Viewing Angle(H/V)	160°/140°
Expected Lifetime	100,000hrs
Service	Rear
IP Rating(Front/Rear)	IP65
Certification	CCC,CE,ETL,RoHS

